

CATAS S.p.A. via Antica, 24/3 33048 San Giovanni al Natisone (UD) +39 0432 747211 - lab@catas.com www.catas.com Testing site: via Braide Matte, 4 33048 San Giovanni al Natisone (UD) tel. +39 0432 747211 lab@catas.com

Date received:

20/09/18

Date of issue:

19/10/18

Report consists of 2 test reports.

Defects before testing: None

Sample name:

RUA DR. ULISSES GUIMARAES 694-ACIBAM 09372-050 SERTAOZINHO-MAUA' () BR - BRAZIL

SQUADRONI PRODUTOS INDUSTRIAIS LTDA.

SQ90 HGA PRETO C/CAPA PISTA PU GRAFITE / SQ90 HGA BLACK WITH COLLAR AND WHEELS

"W' TYPE (SOFT TREAD).

SAMPLE Nº 258519

Overall dimensions: Ø 50 mm

List performed tests:

- 1. Caster/chair base durability test -Cyclic ANSI-BIFMA X5.1-2017/16
- 2. Castors and wheels Impact test EN 12527:1998 clause 4.12



This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director Dr. Andrea Giavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.



CATAS S.p.A. via Antica, 24/3 33048 San Giovanni al Natisone (UD) +39 0432 747211 - lab@catas.com www.catas.com

Testing site: via Braide Matte, 4 33048 San Giovanni al Natisone (UD) tel. +39 0432 747211 lab@catas.com



LAB N° 0027 Membro degli MRA EA IAF e ILAC

TEST REPORT

258519 / 1

Date received: 20/09/18
Date of test: 03/10/18

Date of issue: 19/10/18

Sample name: SQ90 HGA PRETO C/CAPA PISTA PU GRAFITE / SQ90 HGA BLACK WITH COLLAR AND WHEELS

"W" TYPE (SOFT TREAD).

SQUADRONI PRODUTOS INDUSTRIAIS LTDA. RUA DR. ULISSES GUIMARAES 694-ACIBAM 09372-050 SERTAOZINHO-MAUA' BR - BRAZIL

Caster/chair base durability test -Cyclic ANSI-BIFMA X5.1-2017/16

Type of chair: Type III

Clause 16.1 - Pedestal base chair with casters

Seat load: 122 kg

Test results:

Number of cycles	Obstacles	Minimum pull force to separate the caster from the base required N	Pull force to separate the caster from the base measured N	Remarks
2.000	yes	//	<i>II</i>	No defects
98.000	no	22	> 90	No defects

The test results comply with the requirements in clause 16.1.5 of ANSI-BIFMA X5.1-2017

Unless otherwise specified, measurement uncertainty expanded to a confidence level of about 95% is ± 5 N.

The measurement uncertainties stated in this document have been determined according to UNI CEI 70098-3:2016. They were estimated as expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k corresponding to a confidence level of about 95%. Normally k=2.

The test has been carried out with the castors assembled on a plastic star base

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director Dr Andrea Giavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.

pag. 1/1



CATAS S.p.A. via Antica, 24/3 33048 San Giovanni al Natisone (UD) +39 0432 747211 - lab@catas.com www.catas.com Testing site: via Braide Matte, 4 33048 San Giovanni al Natisone (UD) tel. +39 0432 747211 lab@catas.com

BR - BRAZIL

SQUADRONI PRODUTOS INDUSTRIAIS LTDA. RUA DR. ULISSES GUIMARAES 694-ACIBAM

09372-050 SERTAOZINHO-MAUA'

TEST REPORT

258519/2

Date received: 20/09/18
Date of test: 18/10/18

Date of issue: 19/10/18

Sample name:

SQ90 HGA PRETO C/CAPA PISTA PU GRAFITE / SQ90 HGA BLACK WITH COLLAR AND WHEELS

"W" TYPE (SOFT TREAD).



Castors and wheels - Impact test EN 12527:1998 clause 4.12

Castor type: Soft tread wheels type W

Breaking mechanism: yes

Intended use: castors for swivel chairs

Wheel diameter: 50 mm

Apparatus: impact test device and procedures as specified in clause 4.12.3 of EN 12527 standard

Test level: /

Test results:

Sample n°	Drop height mm	Falling mass	Number of drops	Remarks
_1	200	5	10	No defects
2	200	5	10	No defects
3	200	5	10	No defects

The results fulfill the requirements of EN 12529 clause 5.2

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director Dr. Andrea Giavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.

pag. 1/1